

A **KOHLER**, COMPANY

ACCORD_{TM}

Features

- \bullet Compression molded from our exclusive solid Vikrell_ $\!(\!_{\circledcirc}$ material
- Modular 4-piece design
- Pivot "snap together" installation
- · Caulkless installation
- Durable high-gloss finish
- 10-year consumer/3-year commercial limited warranty
- 18" (45.7 cm) bath depth (floor to top of threshold)
- 60-1/4" (153 cm) x 33-1/4" (84.5 cm) x 75-1/2" (191.8 cm) complete unit rough-in dimensions include flanges
- 60" (152.4 cm) x 32" (81.3 cm) x 74-1/4" (188.6 cm) complete unit finished dimensions

Codes/Standards Applicable


Specified model meets or exceeds the following:

- ANSI Z124.1.2
- CSA B45
- ASTM E162
- ASTM E662

60" (152.4 cm) BATH AND WALL SURROUND 71150110 ALSO 71150120



MATERIAL STRENGTH. PROVEN PERFORMANCE,



Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Complete Unit Description	Colors/Finishes	
71150110	60" (152.4 cm) bath and wall surround with left drain	□ 0	☐ Other
71150120	60" (152.4 cm) bath and wall surround with right drain	0	□ Other

$\mathsf{ACCORD}_{\mathsf{TM}}$

Technical Information

Fixture*:					
Bathing well:					
Basin area	21-1/2" (54.6 cm) x 46-1/8" (117.2 cm)				
Top area	23" (58.4 cm) x 51" (129.5 cm)				
To overflow:					
Water depth	13-1/8" (33.3 cm)				
Capacity	56 gal (211.8 L)				
* Approximate measurements for comparison only.					

Mod	lel	door maximum width	door maximum height
1	50110 50120	56-3/4" (144.1 cm)	55-7/8" (141.9 cm)

Installation Notes

Install this product according to the installation guide.

Size the drain cutout to fit the drain assembly that will be used.

End stud positioning is critical.

Studs should be positioned roughly as shown for wall surround installation.

Bath cannot be installed without the wall surround.

