

#### **Features**

- Vitreous china
- Wall-mount
- With hanger
- With overflow
- Drilled for concealed arm carrier
- 8" (203 mm) centers (-8), 4" (102 mm) centers (-4), or single-hole (-1)
- 21-15/16" (557 mm) x 19-3/4" (502 mm)


# **Codes/Standards Applicable**


Specified model meets or exceeds the following:

- ADA
- ICC/ANSI A117.1
- TAS
- CSA B651
- *OBC*
- ASME A112.19.2/CSA B45.1

# **BRENHAM**TM

## WALL-MOUNT BATHROOM SINK WITH SHROUD **K-1999**





## **Colors/Finishes**

- 0: White
- CP: Polished Chrome
- Other: Refer to Price Book for additional colors/finishes

# **Specified Model**

| Model   | Description  | Colors/ | Colors/Finishes |  |  |
|---|--|---------|-----------------|--|--|
| K-1999-1  | Wall-mount bathroom sink with shroud – single-hole                 | 0 🗆     | Other           |  |  |
| K-1999-4  | Wall-mount bathroom sink with shroud – 4" (102 mm) centers         |         |                 |  |  |
| K-1999-8  | Wall-mount bathroom sink with shroud – 8" (203 mm) centers (shown) | 0 🗆     | Other           |  |  |
| Additional lavatories are available without an overflow. Please refer to the KOHLER Price Book. |  |         |                 |  |  |
| Optional Accessories  |  |         |                 |  |  |
| K-8998  | P-trap   | CP      | Other           |  |  |

### **Product Specification**

The wall-mount bathroom sink shall be made of vitreous china. Sink shall be drilled for a concealed arm carrier. Sink shall be 21-15/16'' (557 mm) in length and 19-3/4'' (502 mm) in width. Sink shall be available with 8'' (203 mm) centers (-8), 4'' (102 mm) centers (-4), or single-hole (-1). Sink shall feature an overflow and hanger. Bathroom sink shall be Kohler Model K-1999-\_\_\_\_\_-

# BRENHAM

# **Technical Information**

| Fixture*:                                       |                                      |  |  |  |
|---|--------------------------------------|--|--|--|
| Basin area                                      | 14-3/8" (365 mm) x 12-5/16" (313 mm) |  |  |  |
| Water depth                                     | 3-1/4″ (83 mm)                       |  |  |  |
| Faucet holes                                    |                                      |  |  |  |
| Drain   | Ø 1-3/4″ (44 mm)                     |  |  |  |
| Spout   | Ø 1-3/8″ (35 mm)                     |  |  |  |
| Handle  | Ø 1-3/8″ (35 mm)                     |  |  |  |
| * Approximate measurements for comparison only. |                                      |  |  |  |

#### Recommended ADA/TAS installation:

|   | ADA and TAS  | Children's Environment       |  |  |
|---|--------------|------------------------------|--|--|
|   |              | ADA and TAS Ages<br>6-12 yrs |  |  |
| Α | 34" (864 mm) | 31″ (787 mm)                 |  |  |
| В | 27" (686 mm) | 24" (610 mm)                 |  |  |
| С | 11″ (279 mm) | 11″ (279 mm)                 |  |  |
| D | 9″ (229 mm)  | 9″ (229 mm)                  |  |  |
| E | 8″ (203 mm)  | 8″ (203 mm)                  |  |  |

# **Installation Notes**

**ADA** and **TAS** standards permit parallel approach for children ages 5 years and younger.

Will comply with **ADA** when installed per Section 606 Lavatories of the ADA 2010 Standards for Accessible Design. Will comply with **CSA B651** when installed per Clause 4.3.3 of the standard.

Will comply with **OBC** when installed per Clause 3.8.3.11.

